




● NC10,15,25標準式



● NC30標準式



● NCL10,15,25低床式



型式	荷重 (kg)	フォーク寸法		最低位 (mm)	最高位 (mm)	ステアリング ホイール	ロード ホイール	自重 (kg)
		W(mm)	L(mm)					
NC10-48	1,000	460	810	80	200	ポリウレタン 180Φ×50	ポリウレタン 76Φ×85	65
NC10-49		460	980					69
NC10-58		520	810					65
NC10-59		520	980					69
NC10-510		520	1070					70
NC10-511		520	1150					72
NC10-610		600	1070					76
NC10-710		685	1070					75
NC10-712		685	1220					78
NC15-48		1,500	460					810
NC15-49	460		980	69				
NC15-58	520		810	65				
NC15-59	520		980	69				
NC15-510	520		1070	69				
NC15-511	520		1150	72				
NC15-610	600		1070	76				
NC15-76	685		650	67				
NC15-710	685		1070	75				
NC15-712	685		1220	78				
NC25-58	2,500	520	810	80	200	ポリウレタン 180Φ×50	ポリウレタン 76Φ×85	69
NC25-59		520	980					71
NC25-510		520	1070					71
NC25-610		600	1070					77
NC25-710		685	1070					76
NC25-712		685	1220					79
NC30-510	3,000	520	1070	80	200	ポリウレタン 180Φ×50	(W車輪) 78Φ×70(W)	95
NC30-712		685	1220					99

<低床式> ※NCL15-69はビール専用プラスチックパレット適用車です。

NCL10-58	1,000	520	810	65	165	ポリウレタン 180Φ×50	ポリウレタン 65Φ×85	65					
NCL10-59		520	980					69					
NCL10-510		520	1070					70					
NCL10-610		600	1070					76					
NCL10-710		685	1070					75					
NCL10-712		685	1220					78					
NCL15-58	1,500	520	810	65	165	ポリウレタン 180Φ×50	ポリウレタン 65Φ×85	65					
NCL15-59		520	980					69					
NCL15-69		630	980					76					
NCL15-510		520	1070					70					
NCL15-511		520	1150					72					
NCL15-610		600	1070					76					
NCL15-710		685	1070					75					
NCL15-712		685	1220					78					
NCL25-510		2,500	520					1070	65	165	ポリウレタン 180Φ×50	ポリウレタン 65Φ×85	71
NCL25-610			600					1070					77
NCL25-710	685		1070	76									
NCL25-712	685		1220	79									

フォークアジャスト パレットトラック

NCAJ15	1,500	530~680	1160	80	200	180Φ×50	76Φ×85	80
--------	-------	---------	------	----	-----	---------	--------	----